

Single-Stage Series, 'HD' Air-Cooled and 'HDL' Liquid-Cooled

Model	Single-Seal Double-Seal Triple-Seal	HD082C	HD161 HD162 HD163	HD361 HD362 HD363	HDL362 HDL363	HD602 HD603	HDL602 HDL603	HDL322	HDL342 HDL343	HDL642 HDL643	HD942 HDL942
Number of Cylinders		1	2	2		2		2	2	2	2 (Double Acting)
Bore - in. (mm)		3.0 (76.2)	3.0 (76.2)	4.0 (102)		4.625 (117)		2.0 (51)	2.69 (68)	3.25 (82.5)	4.625 (117)
Stroke - in. (mm)		2.5 (63.5)	2.5 (63.5)	3.0 (76)		4.0 (102)		3.0 (76)	3.0 (76)	4.0 (102)	4.0 (102)
MAWP - psia (bar)		350 (24.1)	350 (24.1)	350 (24.1)		350 (24.1)		1,000 (68.9)	750 (51.7)	750 (51.7)	350 (24.1)
Piston rod dia. - in. (mm)		0.75 (19.1)	0.75 (19.1)	0.75 (19.1)		1.25 (31.8)		0.75 (19.1)	0.75 (19.1)	1.25 (31.8)	1.25 (31.8)
Min./Max. Speed (rpm)		350 / 825	350 / 825	350 / 825		350 / 825		350 / 825	350 / 825	350 / 825	350 / 825
Piston Displacement @ 100 rpm - CFM (m ³ /hr) @ Min rpm - CFM (m ³ /hr) @ Max rpm - CFM (m ³ /hr)		1.02 (1.74) 3.58 (6.1) 8.45 (14.35)	2.05 (3.48) 7.16 (12.2) 16.9 (28.7)	4.36 (7.41) 15.3 (26.0) 36.0 (61.2)		7.78 (13.2) 27.2 (46.3) 64.2 (109.0)		1.09 (2.80) 3.81 (9.8) 9.00 (23.1)	1.97 (5.00) 6.89 (17.51) 16.25 (41.28)	3.84 (6.5) 13.4 (22.8) 31.7 (53.8)	14.99 (25.47) 52.46 (89.1) 125.2 (212)
Max. BHP (kw)		7.5 (5)	10 (7.5)	15 (11)		40 (30)		15 (11)	15 (11)	40 (30)	50 (37)
Approx Wt. w/ Flywheel - lb. (kg)		215 (97)	225 (102)	365 (166)		705 (320)		385 (175)	385 (175)	705 (320)	905 (410)
Inlet & Outlet, NPT - in.		0.75	0.75	1.5" ANSI 300#		2" ANSI 300#		1.5" ANSI 600#	1.5" ANSI 600#	2" 600# ANSI	2" ANSI 300#

Two-Stage Series, 'HD' Air-Cooled and 'HDL' Liquid-Cooled

Model	Double-Seal Triple-Seal	HD172 HD173	HDL172 HDL173	HD372 HD373	HDL372 HDL373	HD612 HD613	HDL612 HDL613
# Cyl. Per Stage		1		1		1	
Bore - in. (mm)	Stage 1 Stage 2	3.0 (76.2) 1.75 (44.5)		4.625 (117) 2.687 (68)		6 (152) 3.25(.83)	
Stroke - in. (mm)		2.5 (63.5)		3.0 (76)		4.0 (102)	
MAWP - psia (bar)		615 (42.4)		615 (42.4)		415 (28.6)	
Piston rod dia. - in. (mm)		0.75 (19.1)		0.75 (19.1)		1.25 (31.8)	
Min. / Max. Speed (rpm)		350 / 825		350 / 825		350 / 825	
Piston Displacement @ 100 rpm - CFM (m ³ /hr) @ Min rpm - CFM (m ³ /hr) @ Max rpm - CFM (m ³ /hr)		1.02 (1.73) 3.57 (6.07) 8.42 (14.3)		2.92 (4.96) 10.2 (17.3) 24.1 (40.8)		6.54 (11.1) 22.9 (38.9) 53.7 (91.2)	
Max. BHP (kw)		10 (7.5)		15 (11)		40 (30)	
Approx Wt. w/ Flywheel - lb. (kg)		245 (111)		405 (184)		775 (352)	
Inlet / Outlet, NPT - in.		0.75 / 0.75		1.25 / 1.00		2.00* / 1.50*	

* NPT or Weld Flanges available

OIL-FREE COMPRESSORS

1809 Century Avenue,
Grand Rapids, MI 49503 U.S.A

(616) 241-1611
Fax (616) 241-3752
www.blackmer.com