



NIMBLE SKID PACKAGE

PRICE LIST
Effective: 5-1-2016
Replaces: 5-1-2015



Neptune Nimble Skids are pre-engineered, factory-assembled pump systems shipped ready for use. The standardized design permits limited customization by selecting the most popular accessories. Skid bases are corrosion-resistant molded polyethylene and piping and accessories are fully supported with stainless steel unistrut. Most existing skid configurations can be shipped within 2 to 3 weeks.

PVC piping is Sch. 80 with 150# socket weld and/or threaded fittings as required for assembly. **MAXIMUM PVC SYSTEM DISCHARGE PRESSURE IS 120 PSI AT 100° F.**

316SS piping is Sch. 40 with 150# threaded fittings. **MAXIMUM 316SS SYSTEM DISCHARGE PRESSURE IS 275 PSI AT 100° F.**

Consult factory for price and limited availability of three pump Nimble Skid systems which can be supplied to a maximum footprint of 24" x 46". Please note that Neptune nimble skid systems are designed & limited to maximum 1/2" pipe!



**** SELECT AND PRICE PUMPS AND ACCESSORIES SEPARATELY ****

A. ELECTRONIC DIAPHRAGM METERING PUMPS

Skid system for use with any one or two Neptune Series **PZ, PW, PZi** or **PZiG** electronic metering pumps. Includes 18" x 30" skid base, 1/2" suction and discharge piping, suction strainer in same MOC as piping, isolation valve(s) in same MOC as piping installed in suction and discharge of each pump, and an appropriate size calibration column.

Basic 1-pump nimble skid ship weight with pump: 75 lbs.

Basic 2-pump nimble skid ship weight: 100 lbs.

| DESCRIPTION | 1-PUMP SKID PRICE List Price / Sch. D | 2-PUMP SKID PRICE List Price / Sch. D |
|--|--|--|
| System with MANIFOLDED PVC suction & discharge piping. Most pumps connected with PVC or PE tubing. | X | |
| System with MANIFOLDED 316SS suction and discharge piping; Pumps connected with SS tubing. | | |
| System with MANIFOLDED PVDF (KYNAR) suction and discharge piping. Pumps connected with rigid piping. | | |
| System with SEPARATE PVC suction and/or discharge piping; pumps connected with polyethylene tubing. | | |
| System with SEPARATE 316SS suction and/or discharge piping; pumps connected with polyethylene tubing. | | |

B. HYDRAULIC DIAPHRAGM METERING PUMPS TO 30 GPH MAXIMUM

Skid system for use with any one or two Neptune Series **500E, 500A** or **500S** simplex hydraulic diaphragm metering pumps to 30 GPH maximum. Includes 18" x 30" skid base, 1/2" suction and discharge piping, suction strainer in same MOC as piping, isolation valve(s) in same MOC as piping installed in suction and discharge of each pump, and appropriate size calibration column.

Basic 1-pump nimble skid ship weight with pump: 100 lbs.

Basic 2-pump nimble skid ship weight: 150 lbs.

| DESCRIPTION | 1-PUMP SKID PRICE List Price / Sch. D | 2-PUMP SKID PRICE List Price / Sch. D |
|---|--|--|
| System with MANIFOLDED PVC suction and discharge piping. Pumps connected with rigid piping. | X | |
| System with MANIFOLDED 316SS suction and discharge piping. Pumps connected with SS tubing. | | |
| System with MANIFOLDED PVDF (KYNAR) suction and discharge piping. Pumps connected with rigid piping. | | |
| System with SEPARATE PVC suction and/or discharge piping; pumps connected with rigid piping. | | |
| System with SEPARATE 316SS suction and/or discharge piping. Pumps connected with SS tubing. | | |



NIMBLE SKID PACKAGE

PRICE LIST
Effective: 5-1-2016
Replaces: 5-1-2015

**** SELECT AND PRICE PUMPS AND ACCESSORIES SEPARATELY ****

C. MECHANICAL DIAPHRAGM METERING PUMPS TO 47 GPH MAXIMUM

Skid system for use with any one or two Neptune Series MP7100-2NX simplex mechanical diaphragm metering pumps to 47 GPH maximum. Includes 18" x 36" skid base, 1/2" suction and discharge piping, suction strainer in same MOC as piping, isolation valve(s) in same MOC as piping installed in suction and discharge of each pump, and appropriate size calibration column.

Basic 1-pump nimble skid ship weight with pump: 110 lbs. Basic 2-pump nimble skid ship weight: 175 lbs.

| DESCRIPTION | 1-PUMP SKID PRICE List Price / Sch. D | 2-PUMP SKID PRICE List Price / Sch. D |
|---|--|--|
| System with MANIFOLDED PVC suction and discharge piping. Pumps connected with rigid piping. | X | |
| System with MANIFOLDED 316SS suction and discharge piping. Pumps connected with SS tubing. | | |
| System with SEPARATE PVC suction and/or discharge piping. Pumps connected with polyethylene tubing. | | |
| System with SEPARATE 316SS suction and/or discharge piping. Pumps connected with SS tubing. | | |

D. NIMBLE SKID ACCESSORIES AVAILABLE AT SCHEDULE 'A' PRICING

| MODEL NO. | DESCRIPTION | LIST PRICE Sch. A |
|------------|---|----------------------|
| RV-PVC-050 | Mount 1/2" PVC relief valve in pump discharge – requires (1) per pump | |
| RV-316 | Mount 1/2" 316SS relief valve in pump discharge – requires (1) per pump | |
| Hose 2 | Parts required to field pipe (2) relief valve outlets to tank (includes loose fittings, clamps, hose barbs and 15 ft. of Nylon reinforced PVC hose) | |

E. NIMBLE SKID ACCESSORIES AVAILABLE AT SCHEDULE 'C' PRICING

| MODEL NO. | DESCRIPTION | LIST PRICE Sch. C |
|---------------|---|----------------------|
| BP-PVC-050 | 1/2" NPT PVC diaphragm-type back pressure valve set at 50 psi | |
| BP-SS | 1/2" NPT 316SS diaphragm-type back pressure valve set at 50 psi | |
| BP-KY | 1/2" NPT PVDF diaphragm-type back pressure valve set at 50 psi | |
| RV-KY | 1/2" NPT PVDF diaphragm-type relief valve | |
| PG-Seal-100 | 2-1/2" dial, 0-100 psi pressure gauge with PVC diaphragm seal | |
| PG-Seal-200 | 2-1/2" dial, 0-200 psi pressure gauge with PVC diaphragm seal | |
| PG-Seal-100KY | 2-1/2" dial, 0-100 psi pressure gauge with PVDF diaphragm seal | |
| PG-Seal-200KY | 2-1/2" dial, 0-200 psi pressure gauge with PVDF diaphragm seal | |
| PG-SNUB | 2-1/2" dial, 0-200 psi pressure gauge with stainless steel snubber | |
| CCG-100-KY | 100 ml calibration column, borosilicate glass, PVDF ends | |
| CCG-200-KY | 200 ml calibration column, borosilicate glass, PVDF ends | |
| 104698 | Polyethylene containment basin – fits 18" x 30" nimble skid system only | |